

(12) **UK Patent Application** (19) **GB** (11) **2 243 381** (13) **A**  
(43) Date of A publication 30.10.1991

(21) Application No 9108244.6

(22) Date of filing 17.04.1991

(30) Priority data  
(31) 513922 (32) 24.04.1990 (33) US

(71) Applicant  
**Structural Panels INC**

(Incorporated In the USA - Florida)

350 Burbank, Oldmar, Florida,  
United States of America

(72) Inventor  
**Stephen C Meyerson**

(74) Agent and/or Address for Service  
**Raworth Moss and Cook**  
36 Sydenham Road, Croydon, Surrey, CR0 2EF,  
United Kingdom

(51) INT CL<sup>a</sup>  
E04B 1/66

(52) UK CL (Edition K)  
E1D DF112 DLEKM2 DLEQW2 D193 D2141 D401  
D402 D421 D501

(56) Documents cited  
GB 2142670 A GB 1347401 A GB 1277965 A  
WO 86/05224 A US 4769963 A

(58) Field of search  
UK CL (Edition K) E1D DF112 DLEKMCV DLEKMDV  
DLEKMNV DLEKMSV DLEQWCV DLEQWDV  
INT CL<sup>a</sup> E04B

(54) Building panel joint

(57) A joint comprises, a ramp 20, pocket 18, which may contain a sealant (34, figures 9 and 10 not shown), an interlocking wedge element 19 and a centering stabilizer 21. In use two insulated panels 11 are locked together by a snap fit causing the wedge 19 to yieldably move over the ramp 20 into the pocket 18 causing the sealant (34), positioned in pocket 18, to extrude forming a gasket between the pocket walls 25 and the wedge 19. The wedge 19 may be formed on one edge of a panel, figure 8, or alternatively may be formed on both sides of an 'I' beam 42 interposed between two panels, figure 15.




FIG. 8




FIG. 15